

FRANCK MULLER
GENEVE

FRANCK MULLER
GENEVE

Curvex CX Bohème



CX 27 SC AT FO CD BOHEME AC AC
AC



Bohème Collection

Reference CX 27 SC AT FO CD BOHEME AC AC

Functions Hours, Minutes, Seconds

Movement MVT 1748
Bidirectional automatic movement
38 hours power reserve
75 components
Diameter: Ø 17,2 mm. Thickness: 4,8 mm
Balance wheel frequency set to 28,800 vibrations per hour

Movement Decoration Côtes de Genève on bridges and the rotor plate
Perlage on the mainplate
Beveling on the rotor board
Diamond polishing on the sinks and bridge bevels
Sunray brushing on the bridges, rotor segment, bearing cage and barrel cover
Snailing on the ratchets

Instructions Dual-Position Crown: 1. Winding. 2. Setting the time

Case Curvex CX Case
Water resistant up to 30 meters
Width: 27 mm. Length: 32.15 mm. Thickness: 7.4 mm
Stainless Steel
Stainless steel internal bezel
Sapphire crystal

Dial Hand set with 12 brilliant-cut diamonds (0.07 carats)
Stamped guilloché with sun pattern
Numerals meticulously applied by hand

Bracelet Alligator Strap

